

JK EC I 22000-24499 GAL NP
Compartment: 1

Shell Full: 23679
2% Outage: 474

| Inches | 0 Feet | 1 Foot | 2 Feet | 3 Feet | 4 Feet | 5 Feet | 6 Feet | 7 Feet |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0.00 | 0 | 1135 | 3323 | 6287 | 9492 | 12859 | 16199 | 19311 |
| 0.25 | 4 | 1170 | 3378 | 6349 | 9556 | 12932 | 16268 | 19363 |
| 0.50 | 10 | 1205 | 3432 | 6418 | 9628 | 13005 | 16336 | 19416 |
| 0.75 | 18 | 1241 | 3491 | 6478 | 9699 | 13074 | 16402 | 19475 |
| 1.00 | 28 | 1277 | 3552 | 6544 | 9772 | 13140 | 16472 | 19535 |
| 1.25 | 40 | 1314 | 3611 | 6605 | 9845 | 13213 | 16541 | 19594 |
| 1.50 | 52 | 1351 | 3668 | 6668 | 9914 | 13282 | 16607 | 19657 |
| 1.75 | 66 | 1388 | 3731 | 6739 | 9987 | 13356 | 16678 | 19720 |
| 2.00 | 80 | 1425 | 3790 | 6805 | 10056 | 13429 | 16749 | 19780 |
| 2.25 | 96 | 1463 | 3849 | 6876 | 10124 | 13497 | 16818 | 19839 |
| 2.50 | 112 | 1501 | 3910 | 6939 | 10196 | 13573 | 16886 | 19899 |
| 2.75 | 129 | 1539 | 3972 | 7008 | 10265 | 13646 | 16951 | 19957 |
| 3.00 | 146 | 1577 | 4036 | 7071 | 10338 | 13717 | 17022 | 20017 |
| 3.25 | 163 | 1616 | 4096 | 7141 | 10409 | 13785 | 17091 | 20075 |
| 3.50 | 182 | 1655 | 4155 | 7207 | 10475 | 13854 | 17157 | 20132 |
| 3.75 | 201 | 1695 | 4217 | 7279 | 10545 | 13926 | 17222 | 20193 |
| 4.00 | 221 | 1735 | 4276 | 7343 | 10625 | 13995 | 17292 | 20252 |
| 4.25 | 242 | 1775 | 4341 | 7412 | 10699 | 14069 | 17361 | 20309 |
| 4.50 | 263 | 1815 | 4403 | 7477 | 10770 | 14141 | 17427 | 20369 |
| 4.75 | 285 | 1829 | 4459 | 7549 | 10847 | 14210 | 17492 | 20429 |
| 5.00 | 308 | 1886 | 4523 | 7616 | 10922 | 14277 | 17562 | 20488 |
| 5.25 | 331 | 1933 | 4581 | 7687 | 10992 | 14348 | 17630 | 20545 |
| 5.50 | 355 | 1978 | 4646 | 7754 | 11070 | 14418 | 17697 | 20602 |
| 5.75 | 379 | 2024 | 4718 | 7825 | 11144 | 14486 | 17762 | 20663 |
| 6.00 | 404 | 2070 | 4796 | 7893 | 11215 | 14559 | 17832 | 20720 |
| 6.25 | 429 | 2115 | 4859 | 7968 | 11291 | 14629 | 17901 | 20777 |
| 6.50 | 455 | 2161 | 4915 | 8038 | 11365 | 14697 | 17968 | 20834 |
| 6.75 | 482 | 2207 | 4974 | 8111 | 11435 | 14762 | 18033 | 20892 |
| 7.00 | 509 | 2252 | 5030 | 8180 | 11510 | 14829 | 18097 | 20949 |
| 7.25 | 536 | 2298 | 5085 | 8254 | 11582 | 14896 | 18162 | 21004 |
| 7.50 | 564 | 2348 | 5144 | 8324 | 11651 | 14960 | 18226 | 21059 |
| 7.75 | 592 | 2392 | 5201 | 8388 | 11725 | 15030 | 18291 | 21116 |
| 8.00 | 621 | 2440 | 5260 | 8458 | 11795 | 15097 | 18352 | 21171 |
| 8.25 | 650 | 2493 | 5323 | 8523 | 11863 | 15164 | 18419 | 21225 |
| 8.50 | 679 | 2543 | 5390 | 8588 | 11938 | 15235 | 18485 | 21279 |
| 8.75 | 710 | 2597 | 5452 | 8654 | 12007 | 15304 | 18549 | 21331 |
| 9.00 | 740 | 2647 | 5522 | 8725 | 12073 | 15370 | 18610 | 21386 |
| 9.25 | 771 | 2701 | 5583 | 8790 | 12144 | 15436 | 18669 | 21439 |
| 9.50 | 802 | 2750 | 5649 | 8859 | 12214 | 15505 | 18733 | 21491 |
| 9.75 | 834 | 2814 | 5710 | 8925 | 12279 | 15573 | 18795 | 21540 |
| 10.00 | 866 | 2871 | 5771 | 8987 | 12342 | 15646 | 18854 | 21592 |
| 10.25 | 898 | 2928 | 5839 | 9052 | 12408 | 15717 | 18911 | 21643 |
| 10.50 | 931 | 2986 | 5901 | 9119 | 12470 | 15785 | 18972 | 21692 |
| 10.75 | 964 | 3042 | 5966 | 9185 | 12530 | 15852 | 19032 | 21738 |
| 11.00 | 997 | 3097 | 6026 | 9246 | 12593 | 15923 | 19090 | 21786 |
| 11.25 | 1031 | 3152 | 6089 | 9308 | 12655 | 15994 | 19145 | 21833 |
| 11.50 | 1065 | 3211 | 6159 | 9369 | 12719 | 16062 | 19203 | 21878 |
| 11.75 | 1100 | 3269 | 6223 | 9434 | 12789 | 16129 | 19258 | 21927 |

ATTENTION

Measurements made using these tables should be verified initially by comparing to metered quantity of product or other means (such as weight). Capacities shown indicate US gallons out of tank at given outage dimension measured from inside top of shell to liquid level at center of tank.

WCHX 23520

OUTAGE GAUGE TABLE

Page 81

EC I 22000-24499 GAL NP
Compartment: 1

Shell Full: 23679
2% Outage: 474

| Inches | 8 Feet | 9 Feet |
|--------|--------|--------|
| 0.00 | 21972 | 23679 |
| 0.25 | 22016 | |
| 0.50 | 22058 | |
| 0.75 | 22098 | |
| 1.00 | 22138 | |
| 1.25 | 22175 | |
| 1.50 | 22214 | |
| 1.75 | 22252 | |
| 2.00 | 22296 | |
| 2.25 | 22343 | |
| 2.50 | 22389 | |
| 2.75 | 22431 | |
| 3.00 | 22476 | |
| 3.25 | 22520 | |
| 3.50 | 22562 | |
| 3.75 | 22602 | |
| 4.00 | 22644 | |
| 4.25 | 22685 | |
| 4.50 | 22724 | |
| 4.75 | 22764 | |
| 5.00 | 22803 | |
| 5.25 | 22840 | |
| 5.50 | 22878 | |
| 5.75 | 22914 | |
| 6.00 | 22950 | |
| 6.25 | 22987 | |
| 6.50 | 23020 | |
| 6.75 | 23051 | |
| 7.00 | 23086 | |
| 7.25 | 23120 | |
| 7.50 | 23154 | |
| 7.75 | 23187 | |
| 8.00 | 23219 | |
| 8.25 | 23252 | |
| 8.50 | 23284 | |
| 8.75 | 23316 | |
| 9.00 | 23347 | |
| 9.25 | 23377 | |
| 9.50 | 23407 | |
| 9.75 | 23436 | |
| 10.00 | 23466 | |
| 10.25 | 23494 | |
| 10.50 | 23522 | |
| 10.75 | 23549 | |
| 11.00 | 23576 | |
| 11.25 | 23602 | |
| 11.50 | 23628 | |
| 11.75 | 23654 | |

Please Note that Gauge Tables do NOT show exact gallons in Tank. This is due to manufacturing Tolerances and shld not affect the overall accuracy of the table.

ATTENTION

Measurements made using these tables should be verified initially by comparing to metered quantity of product or other means (such as weight). Capacities shown indicate US gallons out of tank at given outage dimension measured from inside top of shell to liquid level at center of tank.